

WHALEWATCH

- NOTES:
- ENERGY PATH 1
 - PROVIDE 22" X 36" ATTIC ACCESS, 18" X 24" CRAWL SPACE ACCESS
 - NO LESS THAN 10% BEDROOM LIGHT FROM NATURAL SOURCES
 - PROVIDE MIN. 36" X 36" LANDING AT EGRESS
 - ALL WINDOWS AND PATIO DOORS TO HAVE INSULATED GLAZING
 - BEDROOM WINDOWS SHALL HAVE WINDOW EGRESS OF 5.7 ? MIN. OPENING AND NO MORE THAN 44" A.F.F., A MIN. CLR. WIDTH OF 20" AND MIN. CLR HEIGHT OF 22"
 - INSULATION AS FOLLOWS:
 WALLS: R-21
 UNDERFLOOR: R-25
 FLAT CEILING: R-38
 VAULTED CEILING: R-30
 - ALL EXTERIOR DOORS AND WINDOWS TO HAVE 4 X 8 HEADERS UNLESS SPECIFIED ON PLANS
 - PROVIDE FIRE BLOCKING AS PER LOCAL BUILDING CODE.
 - ALL ELECTRICAL WIRING AS PER LOCAL CODE.
 - ALL PLUMBING AS PER LOCAL CODE.
 - ALL WINDOWS WITHIN 18" OF FINISHED FLOOR AND 12" OF DOORS ARE TO BE TEMPERED GLAZING
 - DESIGN LOADS:
 FLOOR LOADS @ 40 LBS/? LIVE, 12 LBS/? DEAD
 ROOF LOADS @ 25 LBS/? LIVE, 15 LBS/? DEAD

NOTE: ALL WINDOW AND DOOR SCHEDULES REFLECT ONE UNIT ONLY

WINDOW SCHEDULE					
NO.	SIZE:	DESCRIPTION:	LOCATION:	HEAD HT.	QTY.
W/1	2? 2? G	JAMMING	MASTER BATH	6'-8"	1
W/2	2? 2? G	JAMMING	UPPER BATHS	6'-8"	3
W/3	22 22 G	FIXED TRANSOM	GREAT ROOM	10'-6" 1-4	4
W/4	2? 3? G	SINGLE HUNG	MASTER BATH	6'-8"	1
W/5	2? 3? G	SINGLE HUNG	ENTRY HALL	6'-8"	1
W/6	22 4? G	SINGLE HUNG	MASTER BEDROOM	6'-8"	2
W/7	2? 4? G	SINGLE HUNG	UPPER BEDROOMS, GARAGE	6'-8" round	8
W/8	2? 6? G	BOTTOM SLIDER	GREAT ROOM	8'-0"	2
W/9					
W/10	5? 3-6	FIXED TRANSOM	GREAT ROOM	12'-6" 4-1	1
W/11	4? 5?	AGRILIC BLOCK	MASTER BATH	6'-8"	1
W/12	5? 6?	FIXED	GREAT ROOM	8'-0"	1
TOTAL:					29

NOTE: VERIFY ALL WINDOW & DOORS W/ELEVATIONS

DOOR SCHEDULE					
NO.	SIZE:	DESCRIPTION	LOCATION	MODEL #	QTY.
D/1	3? 6?	4-PANEL EXT.	ENTRY		1
D/2	3? 6?	4-PANEL METAL EXT.	GARAGE		1
D/3	2-8 6?	FULL LITE EXT.	GREAT ROOM		1
D/4	2-6 6?	4-PANEL INT.	BEDROOMS		3
D/5	2-4 6?	4-PANEL INT.	CLOSETS, BATHROOMS		4
D/6	6? 6?	PATIO DOOR	MASTER BEDROOM		1
D/7	4? 6?	BI-PASS	UPPER BATH		1
D/8	3? 6?	BI-FOLD	BEDROOM CLOSET		1
D/9	2-4 6?	POCKET DOOR	MASTER BATH		1
TOTAL:					14

